

## Models CS26, CS24, CS20, CS16 – 2" ES & CU-175

### TRACK CONFIGURATIONS & SPACE REQUIREMENTS



**Vertical Lift —**  
Full vertical rise where headroom is available.


**2" Track**

Headroom: Door height plus 14"  
Sideroom: 4 1/2" on wood  
5" on steel

**3" Track**

Headroom: Door height plus 14"  
Sideroom: 5" on wood  
5 1/2" on steel

**Backroom**  
24"



**High Lift —**  
To put horizontal track as close to ceiling as possible.


**2" Track**

Maximum High Lift Equals Headroom Available Minus 18"  
Sideroom: 4 1/2" on wood  
5" on steel

**3" Track**

Maximum High Lift Equals Headroom Available Minus 18"  
Sideroom: 5" on wood  
5 1/2" on steel

Backroom Varies - Consult Distributor



**Standard Lift —**  
For normal installations.

**2" Track**

15" Radius, Headroom: 16"  
12" Radius, Headroom: 14"  
Sideroom: 4 1/2" on wood  
5" on steel

**3" Track**

Headroom: 18"  
Sideroom: 5" on wood  
5 1/2" on steel

**Backroom**  
Door Height plus 20"



**\*Low Headroom —**  
For low clearance installations.

**FRONT TORSION**

**2" Track**

Headroom: 10"  
Sideroom: 6" on wood  
7" on steel

**3" Track**

Headroom: 14"  
Sideroom: 6 1/2" on wood  
7 1/2" on steel

**REAR TORSION**

**2" Track**

Headroom: 7"  
Sideroom: 6" on wood  
7" on steel


**3" Track**

Headroom: 9"  
Sideroom: 6 1/2" on wood  
7 1/2" on steel


**Backroom**

Door Height PLUS 30"  
\*Low Headroom not available on some door sizes, consult distributor.


### TRACK MOUNTING DETAILS




**Bracket Mounted Track —** to attach to wood jambs.



**Reverse Angle Mounted Track —** continuous 3" x 5" angle to attach to steel jambs.




**Angle Mounted Track —** continuous 3" x 5" angle used on larger doors to attach to wood jambs.



**Inclined Track —** To follow pitch of roof.

## Models 3" ES

### TRACK CONFIGURATIONS & SPACE REQUIREMENTS



**Vertical Lift —**  
Full vertical rise where headroom is available.


**2" Track**

Headroom: Door height plus 14"  
Sideroom: 4 1/2" on wood  
5" on steel

**3" Track**

Headroom: Door height plus 14"  
Sideroom: 5" on wood  
5 1/2" on steel

**Backroom**  
24"



**High Lift —**  
To put horizontal track as close to ceiling as possible.


**2" Track**

Maximum High Lift Equals Headroom Available Minus 18"  
Sideroom: 4 1/2" on wood  
5" on steel

**3" Track**

Maximum High Lift Equals Headroom Available Minus 18"  
Sideroom: 5" on wood  
5 1/2" on steel

Backroom Varies - Consult Distributor



**Standard Lift —**  
For normal installations

**2" Track**

15" Radius, Headroom: 17"  
12" Radius, Headroom: 14"  
Sideroom: 4 1/2" on wood  
5" on steel

**3" Track**

Headroom: 18"  
Sideroom: 5" on wood  
5 1/2" on steel

**Backroom**  
Door Height plus 20"



**\*Low Headroom —**  
For low clearance installations.

**FRONT TORSION**

**2" Track**

Headroom: 11"  
Sideroom: 6" on wood  
7" on steel

**3" Track**

Headroom: 14"  
Sideroom: 6 1/2" on wood  
7 1/2" on steel

**REAR TORSION**

**2" Track**

Headroom: 7"  
Sideroom: 6" on wood  
7" on steel


**3" Track**

Headroom: 9"  
Sideroom: 6 1/2" on wood  
7 1/2" on steel


**Backroom**

Door Height PLUS 30"  
\*Low Headroom not available on some door sizes, consult distributor.


### TRACK MOUNTING DETAILS



**Angle Mounted Track —** continuous 3" x 6" angle used on larger doors to attach to wood jambs.



**Reverse Angle Mounted Track —** continuous 3" x 6" angle to attach to steel jambs.



**Inclined Track —** To follow pitch of roof.