

Models CS26, CS24, CS20, CS16 – 2" ES & CU-175

TRACK CONFIGURATIONS & SPACE REQUIREMENTS



Vertical Lift —
Full vertical rise where headroom is available.


2" Track

Headroom: Door height plus 14"
Sideroom: 4 1/2" on wood
5" on steel

3" Track

Headroom: Door height plus 14"
Sideroom: 5" on wood
5 1/2" on steel

Backroom
24"




High Lift —
To put horizontal track as close to ceiling as possible.

2" Track

Maximum High Lift Equals Headroom Available Minus 18"
Sideroom: 4 1/2" on wood
5" on steel

3" Track

Maximum High Lift Equals Headroom Available Minus 18"
Sideroom: 5" on wood
5 1/2" on steel
Backroom Varies - Consult Distributor



Standard Lift —
For normal installations.

2" Track

15" Radius, Headroom: 16"
12" Radius, Headroom: 14"
Sideroom: 4 1/2" on wood
5" on steel

3" Track

Headroom: 18"
Sideroom: 5" on wood
5 1/2" on steel

Backroom
Door Height plus 20"



***Low Headroom —**
For low clearance installations.

FRONT TORSION

2" Track

Headroom: 10"
Sideroom: 6" on wood
7" on steel

3" Track

Headroom: 14"
Sideroom: 6 1/2" on wood
7 1/2" on steel

REAR TORSION

2" Track

Headroom: 7"
Sideroom: 6" on wood
7" on steel


3" Track

Headroom: 9"
Sideroom: 6 1/2" on wood
7 1/2" on steel


Backroom

Door Height PLUS 30"
*Low Headroom not available on some door sizes, consult distributor.


TRACK MOUNTING DETAILS




Bracket Mounted Track — to attach to wood jambs.



Reverse Angle Mounted Track — continuous 3" x 5" angle to attach to steel jambs.




Angle Mounted Track — continuous 3" x 5" angle used on larger doors to attach to wood jambs.



Inclined Track — To follow pitch of roof.

Models 3" ES

TRACK CONFIGURATIONS & SPACE REQUIREMENTS



Vertical Lift —
Full vertical rise where headroom is available.


2" Track

Headroom: Door height plus 14"
Sideroom: 4 1/2" on wood
5" on steel

3" Track

Headroom: Door height plus 14"
Sideroom: 5" on wood
5 1/2" on steel

Backroom
24"




High Lift —
To put horizontal track as close to ceiling as possible.

2" Track

Maximum High Lift Equals Headroom Available Minus 18"
Sideroom: 4 1/2" on wood
5" on steel

3" Track

Maximum High Lift Equals Headroom Available Minus 18"
Sideroom: 5" on wood
5 1/2" on steel
Backroom Varies - Consult Distributor



Standard Lift —
For normal installations.

2" Track

15" Radius, Headroom: 17"
12" Radius, Headroom: 14"
Sideroom: 4 1/2" on wood
5" on steel

3" Track

Headroom: 18"
Sideroom: 5" on wood
5 1/2" on steel

Backroom
Door Height plus 20"



***Low Headroom —**
For low clearance installations.

FRONT TORSION

2" Track

Headroom: 11"
Sideroom: 6" on wood
7" on steel

3" Track

Headroom: 14"
Sideroom: 6 1/2" on wood
7 1/2" on steel

REAR TORSION

2" Track

Headroom: 7"
Sideroom: 6" on wood
7" on steel


3" Track

Headroom: 9"
Sideroom: 6 1/2" on wood
7 1/2" on steel


Backroom

Door Height PLUS 30"
*Low Headroom not available on some door sizes, consult distributor.


TRACK MOUNTING DETAILS



Angle Mounted Track — continuous 3" x 6" angle used on larger doors to attach to wood jambs.



Reverse Angle Mounted Track — continuous 3" x 6" angle to attach to steel jambs.



Inclined Track — To follow pitch of roof.