



Midland's quality-constructed Commercial 2-inch Ribbed Steel overhead doors combine durability, looks and value, to offer outstanding performance at an affordable price. Ribbed CS series doors are available in 20-, 24- and 26-gauge steel. Our state-of-the-art roll-formed manufacturing process adds strength that will last decades.

Available in non-insulated or insulated.

# THE TECHNOLOGY & STRENGTH OF YOUR COMMERCIAL RIBBED STEEL DOOR

Midland's Ribbed CS doors feature embossed pebble-grain exteriors that can be customized with multiple color options and window configurations. All Midland commercial doors feature heavy-duty galvanized steel tracks and hardware.

## CHOOSE YOUR COLOR



White (CS20, CS24, CS26)



Sandtone (CS24)



Coffee (CS24, CS26)



Consult your Midland dealer for custom color options. Due to the printing process, the colors in this brochure may not be exact; contact your Midland dealer for accurate colors.

## ADD WINDOWS




24x12 Plain




24x5 Plain


## TRACK MOUNTING DETAILS



**Bracket Mounted Track**  
To attach to wood jambs




**Reverse Angle Mounted Track**  
Continuous leg-in angle to attach to steel jambs




**Angle Mounted Track**  
Continuous leg-out angle used on larger doors to attach to wood jambs


## TRACK CONFIGURATIONS




**Standard Lift**  
For normal installations



**Inclined Track**  
To follow pitch of roof



**High Lift**  
To put horizontal track as close to ceiling as possible



**Vertical Lift**  
Full vertical rise where headroom is available



**Low Headroom**  
For low-clearance installations

For full commercial track space requirements contact your Midland dealer.

## RIBBED INSULATION

	CS20	CS24	CS26
<b>Foam/Insulate</b>	Plain Steel or T-Bond Insulated	Plain Steel or T-Bond Insulated	Plain Steel or T-Bond Insulated
<b>R-Value</b>	T-Bond = 7.0	T-Bond = 7.0	T-Bond = 7.0
<b>Thickness</b>	2 inches	2 inches	2 inches
<b>Maximum Width</b>	40 feet 2 inches	26 feet 2 inches	16 feet 2 inches
<b>Exterior Steel</b>	20-gauge	24-gauge	26-gauge
<b>Warranty*</b> Excludes Springs	10 years	10 years	25 years



\*For full warranty details contact your Midland dealer.



[www.midlandgaragedoor.com](http://www.midlandgaragedoor.com)

Information shown is based on specifications and features available at the time of printing and is subject to change without prior notice.

© 2018 Midland Garage Door Mfg. Co. Inc. All rights reserved.

0518