

2-INCH THERMOGUARD™

ARCHITECTURAL SPECIFICATIONS



2-INCH THERMOGUARD HIGHLIGHTS

DOOR TYPE: POLYURETHANE INSULATED **PANEL THICKNESS:** 2.0 INCH **R-VALUE:** R18 **INSTALLED U-FACTOR:** 0.14 BTU/HR-FT²-°F
U-Factor is tested per ANSI-DASMA 105. Installed U-Factor and calculated U-Value are NOT equivalent.

SECTION INFORMATION			
STEEL	STANDARDS	SPECIFICATIONS	
Thickness	ASTM A653	Interior: 27 Ga. Exterior: 27 Ga.	20 GA available for both
Embossing		Pebble Texture	
Hot Dipped Galvanized Coating	ASTM A924		
THERMAL BREAKS	TYPE	LOCATION	
Top/Bottom Extrusions	PVC	Top/Bottom Of Sections	
Alcryn	Thermoplastic Elastomer	Bottom Of Sections	
End Stile Seals <i>(Commercial Only)</i>	Polypropylene	Face Side End Of Stiles	
STILES	MATERIAL	SPECIFICATIONS	
End Stiles	HDG Steel	16. Ga.	
Center Stiles	HDG Steel	20. Ga.	
FINISH	TYPE	SPECIFICATIONS	
Prime Coat	Urethane Primer	0.2 mil	
Top Coat	Baked On polyester	0.8 mil	

HARDWARE & COUNTERBALANCE		
HARDWARE	FEATURES	SPECIFICATIONS
Hinges	ASTM A123	G60
Rollers	Floating, Bearing	Nylon Steel
SPRING COUNTERBALANCE	STANDARDS	COMPLIANCE
Helical Wound Coil Springs	ASTM A229	10,000 Cycle Standard 25,000 Cycle Available 50,000 Cycle Available 100,000 Cycle Available
Lift Cables		Galvanized Aircraft Type
Cross Header Shaft	ANSI/DASMA 102	Designed For Appropriate SF

TRACKS, LOCK & WEATHERSTRIP		
TRACK	STANDARDS	SPECIFICATIONS
2 Inch Track	ASTM A653 CS-B G40	Bracket/Angle Mount
3 Inch Track	ASTM A653 CS-B G40	Angle Mount
LOCK	TYPE	SPECIFICATIONS
Slide Lock	Interior Mounted	
Keyed Lock	Optional	
Mini Warehouse	Optional	
WEATHERSTRIP	MOUNTING	LOCATION
U-Shape Astragal	Aluminum Retainer	Bottom Of Door

PERFORMANCE DATA		
FEATURE	STANDARDS	SPECIFICATIONS
Wind Guard Package* <i>*OPTIONAL. **Not available in all sizes, consult factory for unusual requirements.</i>	ANSI/DASMA 108	IBC 2015 Exposure B Building Category II
Installed U-Factor <i>U-Factor is tested per ANSI-DASMA 105. Installed U-Factor and calculated U-Value are NOT equivalent.</i>	ANSI/DASMA 105	0.14 BTU/HR-FT ² -°F
R-Value	ASTM C236	R18
AIR INFILTRATION	STANDARDS	COMPLIANCE
15 mph	ANSI/DASMA 105 ASTM E283	0.05 cfm/ft ²
25 mph	ANSI/DASMA 105 ASTM E283	0.13 cfm/ft ²

DOOR OPTIONS	
FINISH OPTIONS	
Standard Colors	White, Almond, Sandtone, Tera-Bronze, Green, Coffee, Black, Gray, Light Oak, And Dark Oak
ColorSelect	Select Custom Color
Powder Coat	Select Custom Color
ADD-ONS	
• Thermal Glazing	• Bottom Sensing Edge
• High Cycle Springs	• Flexible PVC Dual Flap Header Seal
• Jamb Weatherstrip	• Full Vision Aluminum Sections (White Standard With Optional Anodized, Powder Coat, Or ColorSelect Custom Colors)
• Electric Operators	
• Chain Hoist	

OPERATION	
OPERATOR	TYPE
Pull Rope	Standard Equipment
Chain Hoist or Electric Operators	Optional

As manufactured by Midland Garage Door Mfg. Co. Related structure work, opening preparation, field painting, electrical work falls to the responsibility of other trades. Garage doors should be installed in compliance with Midland Garage Door Mfg.Co. instructions by authorized Midland Garage Door installation professionals.